

SAFETY AND COMPLIANCE TESTING FOR SURESTOP

Tested Sample(s)	: Bicycle Brake Pads
Brand	: SureStop
Model	: SureStop Brakes
Color	: Not Specified
Size	: Not Specified
Vendor P/N	: Not Specified
Country of Origin	: Not Specified
Age Grading	: Not Specified
Children's Product	: Not Specified

Prepared For:

SureStop
8F-2, No. 77 Shizeng N. 1st Road
Taichung, Taiwan



Issue Date: 08 May 2015

Final Report: 659.0001.JIS

This document shall not be reproduced except in full without written approval from ACT Lab LLC




This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009.) The Joint Communiqué is available on publications and resources page of the ILAC website at <http://www.ilac.org>. Accreditation listing and certificate can be found at <http://www.iasonline.org>.

CONCLUSION

(659.0001) – SureStop, SureStop Brakes		
Purpose of Test – Each test performed is intended to check compliance with the following:	Result	Comment
JIS 9301-2010 Cycles – Section 5.2 Brakes	C	

President,



John A. Bogler

SAMPLE IDENTIFICATION

Brand:	SureStop	Job No.:	659.0001
Model Name:	SureStop Brakes	Sample ID No.:	659.0001.001
Vendor Name:	SureStop	Type:	Bicycle Brake Pads
Vendor P/N:	Not Specified	Size (c):	Not Specified
Manufacturer:	Not Specified	Color(s):	Not Specified
Manufacturer P/N:	Not Specified	Weight (g):	Not Specified
Serial No.:	Not Specified	Country of Origin:	Not Specified



DATE AND PLACE OF TEST

Sample(s) received on : 28 January 2014
Testing was initiated on : 31 January 2014
Testing was completed on : 31 January 2014
Testing was performed at : Taicang ACT Sporting Goods Testing Co., Ltd.
Taicang City, Suzhou, Jiangsu Province, China

TEST METHODS

Method for each test conducted is as follows:

- JIS 9301 test was performed according to the JIS 9301/ISO Cycles-Safety Requirements for Bicycles (1996) Requirements for Bicycles standard:
 - Section 5.2 Brakes (JIS)
 - Section 4.6 Brakes (ISO)

TEST RESULTS

C: Compliant; Product meets specified standard NC: Non-Compliant; Product does not meet specified standard NA: Not Applicable to this design NR: Not Requested by the Applicant NP: Not Present	ND: None Detected IC: Inconclusive NT: Not Tested FTR: Further Testing Recommended PPM: Parts Per Million *: See Comments
--	---



JIS 9301: CYCLES

JIS 9301: CYCLES			
<u>Ref. #</u>	<u>Test Description</u>	<u>Result</u>	<u>Observations and Notes</u>
5.2	Brakes	C	
5.2.1	Braking Systems (JIS A 1481.7)	NT	
5.2.2	Hand-Operated Brakes	C	
5.2.2(a)	Brake Lever Position	NA	
5.2.2(b)	Brake Lever Grip Dimension	NA	
5.2.2(c)	Attachment Of Brake Assembly And Cable Requirements	NA	
5.2.2(d)	Brake-Block And Brake-Pad Assemblies - Security Test	C	
5.2.2(e)	Brake Adjustment	C	
5.2.2(e)(1)	Braking Force	C	
5.2.2(e)(2)	Clearance	C	
5.2.2(e)(3)	Rod Brakes	NA	
5.2.3	Coaster Brake Hub	NA	
5.2.4	Strength of Brake System	C	
5.2.4(a)	Hand-Operated Brakes	C	
5.2.4(b)	Coaster Brake Hub	NA	
5.2.5	Braking Performance	C	
5.2.6	Linearity of Coaster Brake Hub	NA	

JIS 9301 Safety Requirements & Test Methods: Brakes						
<u>Sample</u>	<u>Conditions</u>	<u>Run</u>	<u>Speed (RPM)</u>	<u>Speed (Km/hr)</u>	<u>Stopping Distance (m)</u>	<u>Corrected Distance (m)</u>
AA10165	Dry Front & Rear Brakes	1	121.0	15.0	1.98	2.08
		2	134.0	16.6	2.26	1.92
		3	131.0	16.2	2.21	1.97
		4	131.0	16.2	2.46	2.21
		5	130.0	16.1	2.24	2.03
		AVERAGE	129.4	16.0	2.23	2.04
AA10166	Dry Front & Rear Brakes	1	124.0	15.3	1.93	1.91
		2	130.0	16.1	1.93	1.72
		3	132.0	16.3	2.26	1.98
		4	131.0	16.2	2.01	1.77
		5	132.0	16.3	2.16	1.88
		AVERAGE	129.8	16.0	2.06	1.85



JIS 9301 Safety Requirements & Test Methods: Brakes						
Sample	Conditions	Run	Speed (RPM)	Speed (Km/hr)	Stopping Distance (m)	Corrected Distance (m)
AA10166	Dry Rear Brakes	1*	132.0	16.3	3.43	3.12
		2	127.0	15.7	2.79	2.71
		3	129.0	15.9	2.79	2.62
		4	129.0	15.9	3.25	3.09
		5	128.0	15.8	3.20	3.09
		AVERAGE	129.0	15.9	3.09	2.93

JIS 9301 Safety Requirements & Test Methods: Brakes						
Sample	Conditions	Run	Speed (RPM)	Speed (Km/hr)	Stopping Distance (m)	Corrected Distance (m)
AA10165	Wet Front & Rear Brakes	1	130.0	16.1	2.08	1.87
		2	132.0	16.3	2.21	1.93
		3	135.0	16.7	2.18	1.81
		4	130.0	16.1	2.39	2.18
		5	131.0	16.2	2.31	2.07
		AVERAGE	131.6	16.2	2.23	1.97
AA10166	Wet Front & Rear Brakes	1	134.0	16.6	1.85	1.53
		2	129.0	15.9	1.60	1.41
		3	131.0	16.2	1.70	1.46
		4	132.0	16.3	1.73	1.47
		5	133.0	16.4	1.32	1.05
		AVERAGE	131.8	16.3	1.64	1.38
AA10166	Wet Rear Brakes	1	129.0	15.9	3.38	3.22
		2	132.0	16.3	3.35	3.04
		3	130.0	16.1	3.48	3.27
		4	126.0	15.6	2.80	2.77
		5	133.0	16.4	3.25	2.90
		AVERAGE	130.0	16.1	3.25	3.04

END OF REPORT